## **BGA Heat Sink - High Performance Cross-Cut Tape On**





ATS Part#: ATS-55425R-C1-R0

Description: 42.50 x 42.50 x 19.50 mm BGA Heat Sink - High Performance Cross-Cut Tape On

Heat Sink Type: Cross-cut
Heat Sink Attachment: Tape On

Equivalent Part Number: ATS-55425R-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- · Designed for BGAs and surface mount packages
- · Comes preassembled with high performance thermal interface material

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	3.3 °C/W	NA °C/W	NA °C/W	NA °C/W	NA °C/W	NA °C/W	NA °C/W
	Ducted Flow	0	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	42.50 mm	42.50 mm	19.50 mm	N/A mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>ATS-5542</li> <li>(Saint-Go</li> <li>Thermal papplication</li> <li>ATS reserved</li> <li>ATS reserved</li> <li>ATS certification</li> </ul>	25R-C2-R0 is the exbain C675). Derformance data aren. The right to updance. The right to updance.	omponent size. neight from the botto act heat sink assem e provided for refere ate or change its pro ak assembly is RoHS ustom options availa	ably with an equivalence only. Actual percent only and percent of the control of	ent therma	al interface material e may vary by



